



AgriPower

INCORPORATED

PRODUCT LINE FOR CUSTOMERS

1	2	3	4	5	6	7
SYSTEM NAME	AG-125	AG-200	AG-300	AG-500	AG-1MW	AG-1.3MW
SYSTEM DESCRIPTION (1)	COMBUSTOR WITH ONE 125 kW WASTE HEAT GENERATOR	COMBUSTOR WITH ONE 200 kW WASTE HEAT GENERATOR	COMBUSTOR WITH ONE 300 kW WASTE HEAT GENERATOR	COMBUSTOR WITH ONE 500 kW WASTE HEAT GENERATOR	COMBUSTOR WITH ONE 1 MW WASTE HEAT GENERATOR	COMBUSTOR WITH ONE 1.3 MW WASTE HEAT GENERATOR
POWER						
GROSS POWER OUTPUT	125 kW	200 kW	300 kW	500 kW	1 MW	1.3 MW
NET POWER OUTPUT (2)	118 kW	195 kW	285 kW	475 kW	950 kW	1.235 kW
HEAT ENERGY						
MAXIMUM GROSS HEAT ENERGY AVAILABLE FOR HEAT, HOT WATER, STEAM AND CO-GENERATION (3)	UP TO 25 MM BTU/hr	UP TO 25 MM BTU/hr	UP TO 25 MM BTU/hr	UP TO 25 MM BTU/hr	UP TO 25 MM BTU/hr	UP TO 25 MM BTU/hr

FOR ADDITIONAL INFORMATION, PLEASE CONTACT BARRY J. BERMAN, CHIEF EXECUTIVE OFFICER
OFFICE: (516) 829-2000 • MOBILE: (516) 384-2100 • FAX: (516) 487-3163
E-MAIL: BBERMAN@AGRIPOWER.COM • OR VISIT OUR WEB-SITE: WWW.AGRIPOWER.COM

FOOTNOTES:

- (1) SYSTEM SPECIFICATIONS, REQUIREMENTS, PRICING AND AVAILABILITY ARE SUBJECT TO CHANGE AT ANY TIME WITHOUT NOTICE.
- (2) NET OUTPUT OF THE WASTE HEAT GENERATORS DOES NOT REFLECT A REDUCTION OF APPROXIMATELY 25 TO 50 kW PER SYSTEM FOR THE PARASITIC LOAD NECESSARY TO OPERATE EACH SYSTEM'S COMPUTER, MOTORS, FANS, BLOWERS, PUMPS, SCREW AUGERS, ETC.
- (3) HEAT ONLY SYSTEMS ARE AVAILABLE FROM 1 MM BTU/hr UP TO 25 MM BTU/hr (GROSS) AND COMBINED HEAT AND POWER SYSTEMS ARE AVAILABLE FROM 125 kW UP TO 1.3 MW (GROSS).